

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
15 December 2005 (15.12.2005)

PCT

(10) International Publication Number  
**WO 2005/119897 A1**

(51) International Patent Classification<sup>7</sup>: **H02M 7/797**

(21) International Application Number:  
PCT/JP2005/009506

(22) International Filing Date: 18 May 2005 (18.05.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2004-166249 3 June 2004 (03.06.2004) JP

(71) Applicants (for all designated States except US): **TOYOTA JIDOSHA KABUSHIKI KAISHA** [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP). **MITSUBISHI DENKI KABUSHIKI KAISHA** [JP/JP]; 2-3, Marunouchi 2-chome, Chiyoda-ku, Tokyo, 1008310 (JP).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **OYOBE, Hichirosai** [JP/JP]; c/o **TOYOTA JIDOSHA KABUSHIKI**

**KAISHA**, 1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP). **ISHIKAWA, Tetsuhiro** [JP/JP]; c/o **TOYOTA JIDOSHA KABUSHIKI KAISHA**, 1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP). **YANO, Tsuyoshi** [JP/JP]; c/o **TOYOTA JIDOSHA KABUSHIKI KAISHA**, 1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP). **KIMATA, Masahiro** [JP/JP]; c/o **Mitsubishi Denki Kabushiki Kaisha**, 2-3, Marunouchi 2-chome, Chiyoda-ku, Tokyo, 1008310 (JP). **MAJUMDAR, Gourab** [JP/JP]; c/o **Mitsubishi Denki Kabushiki Kaisha**, 2-3, Marunouchi 2-chome, Chiyoda-ku, Tokyo, 1008310 (JP). **YU, Yoshiharu** [JP/JP]; c/o **Mitsubishi Denki Kabushiki Kaisha**, 2-3, Marunouchi 2-chome, Chiyoda-ku, Tokyo, 1008310 (JP).

(74) Agents: **FUKAMI, Hisao** et al.; Fukami Patent Office, Mitsui Sumitomo Bank Minamimorimachi Bldg., 1-29, Minamimorimachi 2-chome, Kita-ku, Osaka-shi, Osaka 5300054 (JP).

[Continued on next page]

(54) Title: **POWER CONVERSION DEVICE AND VEHICLE EQUIPPED THEREWITH**



(57) Abstract: A power conversion portion (10) and a connection portion (20) converting power between a fuel cell (FC) and a battery (BAT) corresponding to dc power supply and a motor generator (MG) corresponding to an ac machine, are configured of a matrix converter. For a power flow pattern requiring that the dc power supply provide high voltage, a switch (SCd) in the connection portion (20) operates in response to a control signal received from a control device (30) to electrically connect a power supply line (LC) to a power supply line (Ld) to connect the fuel cell (FC) and the battery (BAT) in series.

WO 2005/119897 A1